Lecture 2 Interferometry and ALMA

AstroTwin Colombia School 2022
Planet formation and ALMA
dr. Nienke van der Marel
Leiden Observatory

Credits to Logan Francis

Contents

- Introducing ALMA
- Basics interferometry
- ALMA interferometry
- Calibration
- Cleaning/imaging
- Basic CASA inspection
- Continuum vs line
- Detections and non-detections
- Using the ALMA archive

ALMA



ALMA

- Array of 66 antennas in Atacama desert in Chile at 5100m elevation
- Started operations in 2011
- Global collaboration between Europe, North America, Chile and East Asia
- Budget 1.3 billion \$ for operation of 30 years
- Sensitivity 100 times higher and resolution 200 times better than previous interferometers
- Resolution down to 0.01"!
- ALMA:
 - 12m-array: 50 antennas, 10 possible configurations with baselines <16 km
 - 7m array (ACA): 12 antennas
 - Total power array: 4 antennas










ALMA bands


ALMA Bands: atmosphere




40-900 GHz

Why interferometry?

JCMT: single dish (15m)



Why interferometry?



Single dish (15m):

$$R \sim \frac{\lambda}{D} \sim 14'' \gg \text{disk size}$$

Interferometer:


$$R \sim \frac{\lambda}{B} \sim 0.4'' (B = 500 \text{ m})$$

 $\sim 0.02'' (B = 10 \text{ km})$


$$\lambda \sim 1 \, \text{mm}$$

Interferometry

- Interferometers multiply signals from pairs of antennas to obtain samples of a complex function called the Visibility.
- The Visibility is a Fourier
 Transform of the sky brightness.
- The samples measured depend on the antenna separation, orientation, and observing wavelength.
- Imaging require an inverse
 Fourier Transform of the samples and mitigation of sampling sparseness (CLEAN lecture)




Two-element interferometer



- Let's imagine a pair of antennas separated by baseline distance b observing a source in direction s at frequency ν.
- Each antenna collects and amplifies the signal to measure a voltage V oscillating at $\omega = 2\pi\nu$.
- The same signal reaches both antennas, one sees a delay $\tau_{\rm g}$

Two-element interferometer




- The signals are digitized, then multiplied and averaged in a correlator to produce fringes with response R_c.
- Fringe amplitude ∝ Source brightness.
- Fringe phase is sensitive to source position.

$$R_c = \left(\frac{V^2}{2}\right) cos(\omega \tau_g)$$

Complex correlator

- What if we observe an extended source I(s)?
- Cosine correlator is only sensitive to even component of extended sources.
- Add 90° delay to make sine correlator and measure odd component too.







$$R_C = \iint I(\mathbf{s}) \cos(2\pi \nu \mathbf{b} \cdot \mathbf{s}/c) d\Omega = \iint I_E(\mathbf{s}) \cos(2\pi \nu \mathbf{b} \cdot \mathbf{s}/c) d\Omega$$

$$R_s = \iint I(\mathbf{s}) \sin(2\pi v \mathbf{b} \cdot \mathbf{s}/c) d\Omega = \iint I_o(\mathbf{s}) \sin(2\pi v \mathbf{b} \cdot \mathbf{s}/c) d\Omega$$

Bandwidth and fringe tracking



- Finite bandwidth attenuates fringe amplitude away from meridian.
- Earth's rotation moves sources through fringes rapidly.




 Solve both problems by adding extra delay to track a reference "phase center".

Primary beam

- Parabolic antennas are not uniformly sensitive → emission away from primary beam center attenuated.
- Physically track the motion of the source to compensate.






Coordinates

uv-plane coordinates

- Image plane: I and m are angular separations on sky East/West and North/South, respectively.
- Visibility (uv) plane: u and v are spatial frequencies East/West and North/South, respectively.
- u and v are wavenumbers, i.e. the length of a baseline in cycles of the observing wavelength.



Fourier transform


The Fourier transform relationship between the image and uv-plane is now:

$$V(u,v) = \iint I_{\nu}(l,m)e^{-2\pi i(ul+vm)}dldm$$

- Our goal measure I(I,m) from our samples of V(u,v).
- With complete sampling of V(u,v) we could simply apply an inverse Fourier transform to recover I(I,m):

$$I_{\nu}(l,m) = \iint V(u,v)e^{2\pi i(ul+vm)}dudv$$

- Each unique baseline vector **b** measures a different **spatial frequency** determined by the projected baseline length in units of the observing wavelength.
- Assume we observe a point source at a wavelength of 1 mm with a single





-40000 - 20000

20000


 $u(\lambda)$


40000







- Baseline projection changes as the Earth rotates!
- This allows us to fill in the uv-plane over time.







- Baseline projection changes as the Earth rotates!
- This allows us to fill in the uv-plane over time.








- Baseline projection changes as the Earth rotates!
- This allows us to fill in the uv-plane over time.


















Frequency dependence


frequencies).

 The uv-coverage is also dependent on our observing wavelength.

Better resolution can be obtained at shorter wavelengths (higher



0.8 20 0.6 10 m (arcsec) 2 0.4 -250000.2 -50000-200.0 -75000-3020 0 -20(arcsec) -5000050000 $u(\lambda)$




Don't worry! Using data will clarify a lot!

More background

- Interferometry is a deep topic these will help:
 - NRAO Summer School Lectures perfect for beginners, has recorded lectures and slides: https://science.nrao.edu/science/meetings/2018/16th-synthesisimaging-workshop/16th-synthesis-imaging-workshop-lectures
 - Essential Radio Astronomy beginner textbook https://www.cv.nrao.edu/~sransom/web/xxx.html
 - Interferometry and Synthesis in Radio Astronomy extremely technical but comprehensive textbook: https://link.springer.com/book/ 10.1007/978-3-319-44431-4
 - ALMA Documentation See the proposer's guide and primer for easy introduction, and the technical handbook for detailed inquiries. https://almascience.eso.org/documents-and-tools/cycle-9-documents


 $Amp\{V(u,v)\}$ δ Function Constant Gaussian Gaussian

 $Amp\{V(u,v)\}$ elliptical elliptical Gaussian Gaussian Disk Bessel Sharp edges!




- At each u,v point you measure Real and Imaginary (as function of time and frequency)
- The "Real" represents radial variations
- The "Imag" represents azimuthal variations
- Amplitude = sqrt(Real²+Imag²)
- Deprojected baseline = sqrt(u²+v²)

Visibility curve: amp vs uv-distance



Two major issues when Fourier transforming: maximum resolvable scale and incomplete PSF

ALMA interferometry





- ALMA:
 - 12m-array: 50 antennas, 10 possible configurations with baselines <16 km
 - 7m array (ACA): 12 antennas
 - Total power array: 4 antennas

- Every antenna is connected with every antenna (baseline)
- So 3 antennas: 6 baselines, 4 antennas:
 24 baselines, etc.
- Each baseline (interference pattern)
 provides a resolution element or spatial
 scale λ/B (B = baseline length), which
 can be described as point in the u,v plane
- Remember: for observing, you want to 'fill the u,v-plane' as much as possible to cover all possible spatial scales and get a nice clean beam

ALMA: uv-plane

- The u,v-plane can be considered the Fourier transform of the x,y-plane: imaging interferometry data means Fourier transforming it
- The u,v-coverage :
 - The sampling of the u,v-plane: the better it is filled, the more accurate your image will be
 - The Fourier transform of the u,v-coverage gives you your beam or PSF: perfect coverage results in a perfect Gaussian beam, imperfect coverage results in a 'dirty beam' with sidelobes
 - Coverage at long baselines means you are sensitive to small spatial scales: coverage at short baselines means you are sensitive to large spatial scales => you usually cannot have both at the same time!





ALMA interferometry

Table A-1: Angular Resolutions (AR) and Maximum Recoverable Scales (MRS) for the Cycle 7 Array configurations


Config	Lmax		Band 3	Band 4	Band 5	Band 6	Band 7	Band 8	Band 9	Band 10
	Lmin		100 GHz	150 GHz	183 GHz	230 GHz	345 GHz	460 GHz	650 GHz	870 GHz
C43-1	161 m	AR	3.4"	2.3"	1.8″	1.5"	1.0"	0.74"	0.52"	0.39"
	15 m	MRS	28.5"	19.0"	15.4"	12.4"	8.3"	6.2"	4.4"	3.3"
C43-2	314 m	AR	2.3"	1.5"	1.2"	1.0"	0.67"	0.50"	0.35"	0.26"
	15 m	MRS	22.6"	15.0"	12.2"	9.8"	6.5"	4.9"	3.5"	2.6"
C43-3	500 m	AR	1.4"	0.94"	0.77"	0.62"	0.41"	0.31"	0.22"	0.16"
	15 m	MRS	16.2"	10.8″	8.7"	7.0"	4.7"	3.5"	2.5"	1.9"
C43-4	784 m	AR	0.92"	0.61"	0.50"	0.40"	0.27"	0.20"	0.14"	0.11"
	15 m	MRS	11.2"	7.5"	6.1"	4.9"	3.3"	2.4"	1.7"	1.3"
C43-5	1.4 km	AR	0.54"	0.36"	0.30"	0.24"	0.16"	0.12"	0.084"	0.063"
	15 m	MRS	6.7"	4.5"	3.6"	2.9"	1.9"	1.5″	1.0"	0.77"
C43-6	2.5 km	AR	0.31"	0.20"	0.16"	0.13"	0.089"	0.067"	0.047"	0.035"
	15 m	MRS	4.1"	2.7"	2.2"	1.8"	1.2"	0.89"	0.63"	0.47"

Each configuration has a limited number of baseline lengths, or a limited number of spatial scales you are sensitive to

MRS: maximum recoverable scale AR: angular resolution

Dirty beam


u,v-coverage (example: SMA with 8 antennas)




Beam or PSF

- ALMA simulation in CASA: provide an image and the details of the requested observations (configuration, integration time, declination of source, frequency) and compute how your image would look like when observed
- Two main differences between convolution and ALMA simulation: spatial scales + side lobes
- Difference generally gets worse in more extended configurations: less u,v-coverage at long baselines

u,v-coverage 5h ALMA observation







Note that only 2/3 of total flux is recovered in C8




- Interferometers have a spatial sampling and beam shape determined by their configuration.
- Extended array configurations (large uv-distances) sample small scales.
- Compact array configurations (small uv-distances) sample large scales.




Fourier Domain (uv-plane) Sampling
















Resolution = 0.2"

Max baseline = 2 km

Interferometry






Antenna positions

Resolution = 0.6"


Max baseline = 600 m





Resolution = 0.03"

Max baseline = 12 km





Interferometry

Convolution

About spectral windows

Lower and upper side band with multiple spectral windows






In each spectral window


About spectral windows

Heterodyne receiver: mixing local oscillator




- Frequency spectral windows always within USB and LSB: LO +/- IF (IF~4-8 GHz)
- ALMA: B9 double, other bands dual SB: freedom in frequency range

About spectral windows



- Basic setup: 4 basebands of 3840 channels each around LO frequency
- Max 4 spectral windows within each baseband
- Compromise: bandwidth (line width, multi-line coverage, continuum bandwidth) or spectral resolution (velocity resolution)
- Observing frequency: depends on Earth velocity at time of observing, so sometimes multiple spectral windows when observed multiple times



Calibration

- We measure amplitudes and phases of sources
- Time dependent:
 - Weather
 - Atmosphere
 - Antenna response
 - Instrument response
 - Moving antennas
 - Etc.



- So we have to calibrate for each antenna all the time
- ALMA calibration is done for you (QA2) so basics only now

Observatory calibrations

- These are done rarely, or when antennas are moved.
- For each antenna, calibration measurements are made for:
 - Array Position
 - Focus
 - Pointing/astrometry
 - Surface accuracy
 - Primary beam pattern



Science observation calibrations

- The following calibrations are done for every ALMA observation:
 - Data Flagging
 - System temperature Measurement
 - Water Vapor Radiometer Corrections
 - Bandpass Calibration
 - Flux Density Scale Calibration
 - Phase (gain) Calibration
 - Check source observations (long-baseline/high frequency only)
 - Polarization Calibrations (polarization observations only)
 - Self-Calibration (ALMA user applied! Friday Workshop :))


0

We'll go through (most of them) one at a time.




Data flagging

- Some problems can completely ruin data, e.g:
 - Broken antennas
 - Correlator glitches
 - Telescope shadowing
 - Radio Frequency Interference
 - Bad calibration solutions
- When this happens, the bad data is removed or "flagged".




System temperature


- System temperature = noise added to observations.
- $T_{sys} = T_{bg} + T_{sky} + T_{spill} + T_{loss} + T_{cal} + T_{rx}, where:$
 - T_{bg} = noise contribution from microwave and galactic backgrounds
 - T_{skv} = noise contribution from atmospheric emission
 - T_{spil} = noise contribution due to ground radiation (spillover and scattering)
 - T_{loss} = noise contribution due to losses in feed
 - T_{out} = noise contribution due to injected noise
 - T_{rx} = receiver noise temperature
- Need to measure T_{sys} to get correct data weights!
- Measure calibrator hot/cold "loads" (resistors) and sky contribution.



Water vapor


- Variations in water vapor in antenna LOS causes significant phase errors:
- ALMA 12m antennas have radiometers that measure water along LOS every 1.1s to correct for this:





Calibrator source


 Flux, bandpass, and phase (gain) calibration vary on short timescales and require observing additional calibrator targets:





Flux calibration


Flux Calibration

- Ideally: observe a mm source of known brightness and scale our visibility amplitudes.
- Problem: the mm sky has few suitable calibrators!
- Option 1: Solar System bodies
- Pros: bright, flux known to 5%
- Cons: not always observable, low flux on long baselines...










Baseline length


Flux calibration

Flux Calibration

- Option 2: Quasars
- Pros: Bright, point-like, all over the sky
- Cons: Time variable Flux!
- ALMA's solution: Observe many quasars regularly with solar system objects in "grid" over the sky.
- Observing an ALMA grid quasar with science targets provides ~10% accuracy at 233 GHz (band 6)




Baseline length



Bandpass calibration


- Correct Amplitude and Phase across bandpass by observing a calibrator.
- Usually done once before/after science target observations.




Phase calibration

Phase (gain) Calibration

- Atmospheric turbulence causes large, time variable phase observations during an observation.
- Short science target scans are bracketed by observations of a phase calibrator.
- Calibration solutions are interpolated in time to science observations.





How do we image ('clean') visibility data?



Recall: sampling

Effects of Sampling

Describe sampling of uv-plane with function S(u,v):


$$V_{\text{obs}} = S(u, v)V(u, v)$$
 $S(u, v) = \sum_{i} \delta(u - u_i, v - v_i) + \delta(u + u_i, v + v_i)$

• If we take the Fourier transform of V_{obs}, we obtain the true sky brightness convolved with the Fourier transform of S:

$$B(l,m) = \mathcal{F}\{S(u,v)\} \qquad I * B = \mathcal{F}^{-1}\{SV\}$$

 B is known as the "dirty beam" or "synthesized beam" and is how the array sees a point source. I*B is thus called the "dirty image".

Dirty image




Dirty image

I(l,m) (a)	B(l,m) (b)	I(l,m)*B(l,m) (c)
•		
Map	Beam	Dirty Map
V(u,v) (d)	S(u,v) (e)	V(u,v)S(u,v) (f)
Visibility	Sampling Function	Sampled Visibility

Image units for radio astronomy


- A Jansky (Jy) is a unit of spectral flux density for radio telescopes.
- Image units are often in Jy/beam, a unit of spectral intensity.
- The beam is the solid angle of the telescope point spread function.
- Flux is calculated by integrating the intensity over the angular extent of the source.

$$1 \, \mathrm{Jy} = 10^{-26} \, rac{\mathrm{W}}{\mathrm{Hz \cdot m^2}}$$



What is the beam?

- For interferometers, the beam size of the synthesized beam main lobe.
- The Full-width at half-maximum (FWHM) of a Gaussian fit to the main lobe is typically used.
- For interferometers, the single dish response is called the primary beam.



Weighting schemes visibilities

(Super-uniform)

- Extreme uniform
- Careful with image quality

Uniform

- Based on uvcoverage
- Smaller beam
- Lower PS sensitivity
- Problems sampling
- Suitable for high S/N

Briggs Robust = +0.5 (-2 ... +2)

- Compromise between resolution and sensitivity
- 'Default'

Natural

- Based on noise-level
- Larger beam
- Higher PS sensitivity
- Suitable for low S/N (weak lines!)


(Tapering)

- Less weight to long baselines: extended structures
- Less relevant in disk studies until <0.1" data

Examples weighting

We typically include the weights in our expression for the sampling function:

$$S(u,v) = \sum_{i} w_i \left(\delta(u - u_i, v - v_i) + \delta(u + u_i, v + v_i) \right)$$



Weighting schemes - natural

- Not all data is created equally each visibility sample has an uncertainty determined during calibration.
- A "Natural" weighting scheme weights the i'th according to its uncertainty:

$$w_i = \frac{1}{\sigma_i^2}$$

Natural weighting provides optimal sensitivity for point source detection.

Weighting schemes - uniform

- The dirty beam has large sidelobes due to the sparseness of uv-plane sampling.
- This can be mitigated by increasing the weight of sparsely sampled regions of the uv-plane: $w_i = \left(\frac{1}{\sigma_i^2}\right)/W_k$

W_k is the local density of data points in the uv-plane, which has been binned into k cells of size 2/FOV.

Uniformly weighting data increases the image noise.

Weighting schemes - briggs


- Brigg's weighting scheme attempts to find a good compromise between uniform and natural weightings.
- The "robustness" parameter R takes values between -2 (essentially uniform) and 2 (essentially natural).

$$\omega_i = rac{1}{\sigma_k^2} \quad w_i = rac{\omega_i}{1+W_k f^2} \quad f^2 = rac{(5*10^{-R})^2}{rac{\sum_k W_k^2}{\sum_i \omega_i}}$$

 R=0.5 provides a good compromise for most ALMA data, but you should experiment and choose what's best for your data!

Weighting schemes - tapering


- Long baselines may contribute significantly to high sidelobes in the dirty beam.
- Short baselines recover extended structures which may be of interest.
- We can optimize for this by multiplying our data weights in the uv-plane by a Gaussian, thus "tapering" out the effect of long baselines.
- This throws away data and increases noise!



Examples weighting


We typically include the weights in our expression for the sampling function:

$$S(u,v) = \sum_{i} w_i \left(\delta(u - u_i, v - v_i) + \delta(u + u_i, v + v_i) \right)$$



The CLEAN algorithm


 The CLEAN algorithm (Hogbom 1974) attempts to deconvolve the image and remove the effects of the dirty beam.



See http://nesanders.github.io/gICLEAN/examples.html

- 1. Produce an initial dirty image I D
- 2. Find brightest point I₀ in I_D
- 3. Subtract from the image the dirty beam B scaled and shifted to peak at γI_0 , where $\gamma < 1$.
- 4. Add a point source of brightness γI_0 to "clean" model image.
- 5. Repeat Steps 2-4, replacing I $_{\rm D}$ with the subtracted map from the last iteration. Stop when I $_{\rm O}$ is comparable to the noise level in the map.
- 6. Convolve the "clean" model with an ideal "clean" beam, typically a Gaussian fit to the main lobe of the dirty beam.
- 7. Add dirty image residuals to clean image.


CLEAN in action



Left: residual image. Right: Removed model x Dirty beam


CLEAN in action

- CLEAN provides an impressive increase in image quality!
- CLEAN works well because we know our images are sparse and mostly empty of emission.




CLEAN and **CASA**

- Using CLEAN with ALMA data is usually done with the CASA package.
- Set of C++ tools for radio data reduction with python bindings.
- Includes it's own python installation.
- Formerly python 2, new versions will use python 3.
- Documentation:
- https://casa.nrao.edu/casadocs/casa-6.1.0
- CASA Tutorials:
 https://casaquides.nrao.edu/index.php?title=Main_Page



CASA basics

- Interface provides an ipython interpreter and GUI output logger.
- Radio reduction tools available as "tasks" i.e. python functions.
- Useful commands:
 - execfile(scriptname) execute commands in a script
 - inp taskname check task inputs
 - help(taskname) get task documentation in terminal
 - doc('taskname') get task documentation in web browser
 - go taskname run task with current inputs
 - tget taskname get inputs last used to run task



CLEAN in CASA


- CLEAN can be used through task tclean in CASA.
- Huge number of inputs but only a handful at a time are needed.

```
Name of input visibility file(s)
                             True
                                            Enable data selection parameters
                                            field(s) to select
                                            spw(s)/channels to select
                                            Range of time to select from data
                                            Select data within uvrange
                                            Select data based on antenna/baseline
                                            Scan number range
                                            Observation ID range
                                            Scan Intent(s)
datacolumn
                    = 'corrected'
                                            Data column to image(data,corrected)
1 magename
                                            Pre-name of output images
imsize
                            [100]
                                            Number of pixels
cell
                                            Cell size
                       'larcsec'
                                            Phase center of the image
phasecenter
                             '1'
                                            Stokes Planes to make
stokes
projection
                            'SIN'
                                            Coordinate projection
                                            Name of starting model image
startmodel
                            'mfs'
                                            Spectral definition mode
                                             (mfs,cube,cubedata, cubesource)
                                            Reference frequency
                       'standard'
                                            Gridding options (standard, wproject,
                                             widefield, mosaic, awproject)
                                            Name of Voltage Pattern table
                             0.2
                                            PB gain level at which to cut off
                                             normalizations
                                            Minor cycle algorithm (hogbom,clark,m
                         'hogbom'
                                             ultiscale, mtmfs, mem, clarkstokes)
                            True
                                            Do restoration steps (or not)
                              П
                                            Restoring beam shape to use. Default
                                            is the PSF main lobe
                                            Apply PB correction on the output
                            False
                                             restored image
outlierfile
                                            Name of outlier-field image
                                             definitions
                        'natural'
                                            Weighting scheme
                                             (natural, uniform, briggs,
                                             briggsabs[experimentall]
                              []
                                            uv-taper on outer baselines in uv-
                                             plane
                                            Maximum number of iterations
                           'user'
                                            Type of mask(s) for deconvolution:
                                             user, pb, or auto-multithresh
                                            Mask (a list of image name(s) or
                                             region file(s) or region string(s)
                             0.0
                                            primary beam mask
fastnoise
                                            True: use the faster (old) noise
                             True
                                             calculation. False: use the new
                                             improved noise calculations
restart
                            True
                                            True : Re-use existing images. False
                                            : Increment imagename
savemodel
                           'none'
                                            Options to save model visibilities
                                             (none, virtual, modelcolumn)
calcres
                                            Calculate initial residual image
                            True
calcpsf
                            True
                                            Calculate PSF
parallel
                            False
                                            Run major cycles in parallel
```

- Most parameters for tclean can be left as default.
- Pay attention to datacolumn 'corrected' contains calibrated data, if present.
- field defaults to select every observed source (a bad idea)
- spw selects all channels/windows by default fine if there are no spectral lines

# tclean :: Radio				
vis			#	Name of input visibility file(s)
selectdata		True	#	Enable data selection parameters
field			#	field(s) to select
spw		4.0	#	spw(s)/channels to select
timerange			#	Range of time to select from data
uvrange			#	Select data within uvrange
			#	Select data based on antenna/baseline
			#	Scan number range
observation			#	Observation ID range
		**	#	Scan Intent(s)
datacolumn	-	'corrected'	#	Data column to image(data,corrected)
imagename	=		#	Pre-name of output images
imsize	-	[100]	#	Number of pixels
cell		['larcsec']	#	Cell size
phasecenter	- 1		#	Phase center of the image
stokes		'I'	#	Stokes Planes to make
projection	-	'SIN'	#	Coordinate projection
startmodel	-00		#	Name of starting model image

- Specmode:
 - 'mfs' = multifrequency synthesis used for continuum
 - 'Cube' used to image spectral lines
- reffreq reference frequency of image defaults to average across selected spw
- pbcor correct for antenna primary beam important for sources on field edge.




Weighting - 'natural', 'uniform' and 'briggs' available (and others...).

```
# Weighting scheme
# (natural,uniform,briggs,
# briggsabs[experimental])
robust = 0.5 # Robustness parameter
npixels = 0 # Number of pixels to determine uv-cell
# size


uvtaper = [] # uv-taper on outer baselines in uv-
# plane
```


- niter just set to some huge number if you don't know what to use
- threshold can be used to instead of niter, e.g '3 mJy', set to expected noise level in image.
- Interactive Set to "True" to show GUI interface

niter	= 9	999 #	Maximum number of iterations
gain		0.1 #	Loop gain
threshold		0.0 #	Stopping threshold
nsigma		0.0 #	Multiplicative factor for rms-based
ar Control of the Con		#	threshold stopping
cycleniter		-1 #	Maximum number of minor-cycle
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		#	iterations
cyclefactor		1.0 #	Scaling on PSF sidelobe level to
87		#	compute the minor-cycle stopping
		#	threshold.
minpsffraction	= 0	.05 #	PSF fraction that marks the max depth
The second secon		#	of cleaning in the minor cycle
maxpsffraction		Θ.8 #	PSF fraction that marks the minimum
The state of the s		#	depth of cleaning in the minor cycle
interactive	= Fa	lse #	Modify masks and parameters at
		#	runtime
			1.30(11)(40)(4)




```
INFO
            ...fineImage
                         Impars : start
INFO
            ...fineImage
                         Shape : [100, 100, 1, 1] Spectral : [3.43505e+11] at [0] with increment [1.58443e+10]
INFO
            ...fineImage
                         Set Gridding options for [Serpens 08] with ftmachine : gridft
INFO
                        Set imaging weights : Briggs weighting: sidelobes will be suppressed over full image
            ... rweight()
INFO
            ...gWeight()
                        Normal robustness, robust = 0.5
INFO
            ...nvolution
                       Set Deconvolution Options for [Serpens 08] : hogbom
            ...Iteration
                         Set Iteration Control Options
INFO
INFO
            ...: : makePSF
                        [Serpens 08] Theoretical sensitivity (Jy/bm):0.000533952
INFO
            ...nsitivity
            ...ntBeamSet
INFO
                         Beam : 5.82657 arcsec, 2.88889 arcsec, -78.1369 deg
                        vi2 : Evaluating Primary Beam model onto image grid(s)
INFO
            ...imaryBeam
            ...ajorCycle
                        ----- Run Major Cycle 1 -----
INFO
            ..mageStats
                         [Serpens 08] Feak residual (max,min) over full image: (0.94841,-0.264522)
INFO
INFO
            ...mageStats
                         [Serpens_08] Total Model Flux : 0
INFO
            ...setupMask
                         [Serpens 08] Initializing new mask to 0.0 for interactive drawing
INFO
            ...setupMask
                         [Serpens_08] Number of pixels in the clean mask : 0 out of a total of 10000 pixels. [ 0 % ]
INFO
            ...ctivemask
                         [Serpens 08.mask] Mask modified from 0 pixels to 510 pixels
INFO
            ...teraction
                         [Serpens 08] Mask changed interactively.
INFO
            ...mageStats
                         [Serpens 08] Peak residual (max,min) within mask : (0.94841, -0.118535) over full image : (0.94841, -0.264522)
INFO
            ..mageStats
                         [Serpens_08] Total Model Flux : 0
INFO
            ...inorCycle
INFO
                         [Serpens 08] Run Hogbom minor-cycle | CycleThreshold=0.367768, CycleNiter=100, Gain=0.1
            ...econvolve
INFO
            ...econvolve
                         [Serpens 08] iters=0.>10 [10], model=0.>0.61882, peakres=0.94841.>0.333689, Reached cyclethreshold.
INFO
            ...ionRecord Completed 10 iterations.
```






Tclean results



Line cleaning


Use specmode='cube' and subparameters to image spectral data




```
'cube'
                                      Spectral definition mode
                                       (mfs,cube,cubedata, cubesource)
                                      Number of channels in the output
                                       image
               - '-20km/s'
                                      First channel (e.g. start=3,start='1.
                                      1GHz', start='15343km/s')
                    2km/s
                                      Channel width (e.g. width=2,width='0.
                                       1MHz', width='10km/s')
                                      Spectral reference frame in which to
                                      interpret 'start' and 'width'
                                      Velocity type (radio, z, ratio, beta,
                    'radio'
                                       gamma, optical)
              230.538GHz
                                     List of rest frequencies
interpolation = 'linear'
                                      Spectral interpolation
                                     (nearest, linear, cubic)
                                   # Number of channel chunks
                             True #
                                     whether to calculate weight density
                                       per channel in Briggs style
                                       weighting or not
```

Multiscale

- CLEAN creates models of the sky using collections of point sources.
- This is not optimal for very extended sources.
- Multiscale cleaning allows CLEAN to use extended Gaussian-like functions for creating a model.




- Measurement set: folder structure which can only be read/edited with CASA!
- Usual extension .ms but can be anything: convenient
- Do NOT change any of data or names inside folder or it becomes unreadable




listobs(vis='mydata.ms') => basic observational data in logger

Tme	Priority	Origin	Mesange
2020-09-22 23:51:55 1	INFO	listobs::::	
2020-09-22 23:51:55 1	INFO	listobs::::+	*48**4#***4#***4***********************
2020-09-22 23:51:55 1	INFO	listobs::::+	##### Begin Task: listobs #####
2020-09-22 23:51:55 1	INFO	listobs::::	listobs(vis="amaur_timebin.ms",selectdata=true,spu='',field='',antenna='",
2020-09-22 23:51:55 1	INFO	listobs::::+	uvrange="",timerange="",correlation="",scan="",intent="",
2020-09-22 23:51:55 1	INFO	listobs::::+	feed="",array="",observation="",verbose=True,listfile="",
2020-09-22 23:51:55 1	INFO	listobs::::+	listunfl-False, cachesize-50, overwrite-False)
2020-09-22 23:51:55 1	INFO	.ms::summary	
2020-09-22 23:51:55 1	INFO	s::summary+	MeasurementSet Name: /Users/nienke/Documents/ALMA/Demo-ABAur/ABAur timebin.ms MS Version 2
2020-09-22 23:51:55 1	INFO	.s::summary+	
2020-09-22 23:51:55 1		s::summary+	Observer: vawentang Project: uid://A001/xa0/x612
2020-09-22 23:51:55 1	INFO	s::summaryt	Observation: ALMA
2020-09-22 23:51:55 1		s::summary+	
2020-09-22 23:51:55 1	INFO	s::summary+	Telescope Observation Date Observer Project
2020-09-22 23:51:55 1		s::summary+	ALMA 4.91456e+09; 4.91456e+09; yawentang uid://a001/xa0/x612
2020-09-22 23:51:55 1		s::summary+	ALMA [4.94376e+09, 4.94377e+09] yawentang uid://A001/Ka0/X512
2020-09-22 23:51:55 1		Properties	Computing scan and subscan properties
2020-09-22 23:51:55 1		.ms::summarv	pata records: 130584 Total elapsed time = 2.92084e+07 seconds
2020-09-22 23:51:55 1	INFO	s::summaryt	Observed from 12-Aug-2014/10:38:53.1 to 16-Jul-2015/12:06:13.4 (DTC)
2020-09-22 23:51:55 1		.ms::summary	
2020-09-22 23:51:55 1		s::summary+	ObservationID = O ArrayID = O
2020-09-22 23:51:55 1		s::summary+	Date Timerange (UTC) Scan Fidid Fieldwane news Spwids Average Interval(s) Scanintent
2020-09-22 23:51:55 1		s::summary+	12-Aug-2014/10:38:53.1 - 10:44:41.1 11 0 ab aurigae 15120 [0,1,2,3] [56.7, 56.7, 56.7, 56.7] [OBSERVE TARGET#ON SOURCE]
2020-09-22 23:51:55 1		_s::summary+	10:45:47.0 = 10:52:38.6 13 0 ab_surigae 17640 [0,1,2,3] [57.5, 57.5, 57.5, 57.5] [OBSERVE_TARGET#ON_SOURCE]
2020-09-22 23:51:55 1		s::summary+	10:56:30.0 - 11:02:18.0 18 0 ab surigae 15120 [0,1,2,3] [56.7, 56.7, 56.7, 56.7] [OBSERVE TARGETTON SOURCE]
2020-09-22 23:51:55 1		s::summary+	11:03:24.1 - 11:10:15.7 20 0 ab_aurigae 17640 [0,1,2,3] [57.5, 57.5, 57.5, 57.5] [OBSERVE_TARGET ON_SOURCE]
2020-09-22 23:51:55 1		s::summary+	11:13:53.3 - 11:19:41.3 25 0 ab_aurigae 15120 [0,1,2,3] [56.7, 56.7, 56.7, 56.7] [OBSERVE_TARGET#ON_SOURCE]
		s::summary+	11:20:46.3 - 11:21:48.3 27 0 ab surigae 2520 [0.1,2,3] [62, 62, 62, 62] [OBSERVE TARGETION SOURCE]
		.ms::summary	
2020-09-22 23:51:55 1		s::summary+	ObservationID = 1 ArrayID = 0
2020-09-22 23:51:55 1		s::summary+	Date Timerange (UTC) Scan FldId FieldName aRows SpwIds Average Interval(s) ScanIntent
2020-09-22 23:51:55 1		s::summary+	16-Jul-2015/11:45:40.0 - 11:50:56.2 28 0 ab_surigae 14820 [4,5,6,7] [62, 62, 62, 62] [OBSERVE_TARGETION_SOURCE]
2020-09-22 23:51:55 1		s::summary+	11:52:02.9 - 11:58:54.4 30 0 ab_aurigae 20748 [4,5,6,7] [57.4, 57.4, 57.4, 57.4] [OBSERVE_TARGET#ON_SOURCE]
2020-09-22 23:51:55 1		s::summary+	12:02:32.5 - 12:06:13.4 35 0 ab aurigae 11856 [4.5,6.7] [54.1, 54.1, 54.1, 54.1] [OBSERVE TARGET ON SOURCE]
2020-09-22 23:51:55 2		.ms::summary	(nBows - Total number of rows per scan)
		.ma::summary	,
2020-09-22 23:51:55 1		s::summary+	ID Code Name RA Becl Epoch Sreld nRows
		s::summary+	0 nome ab aurigae 04:55:45.848188 +30.33.03.92532 J2000 0 130584
2020-09-22 23:51:55 1	INFO	.ms::summarv	
2020-09-22 23:51:55 1		s::summary+	SpwID Name #Chans Frame ChO(MHz) ChanNid(kHz) TotBW(kHz) CtrFreq(MHz) BBC Num Corrs
2020-09-22 23:51:55 1		s::summary+	O ALMA RB 07#BB 1#SW-01#FULL RES 3840 TOPO 345789.363 15.259 58593.8 345818.6522 1 XX XX
2020-09-22 23:51:55 1		s::summary+	1 ALMS RB 07#BB 2#SW-01#FULL RES 960 TGPO 342585.556 1953.125 187500D.0 343522.0798 2 XX XX
2020-09-22 23:51:55 1		s::summary+	2 ALMR NB 07#BB 3#8W-01#FULL NBS 3840 TOPO 330629.728 -15.259 58593.8 330600.4391 3 XX XX
2020-09-22 23:51:55 1		s::summary+	3 ALMA RE 07#BB 4#SW-01#FULL RES 128 TOPO 333004.681 -15625.000 2000000.0 332012.4935 4 XX XX
		s::summary+	4 ALMA RB 07#BB 1#SW-01#FULL RES 3840 TGPO 345770.042 15.259 58593.8 345799.3317 1 XX XX
2020-09-22 23:51:55 1		s::summary+	5 ALMA NB 07#BB 2#8W-01#FULL NBS 960 TOPO 342575.939 1953.125 1875000.0 343512.4623 2 XX YY
2020-09-22 23:51:55 1		s::summary+	6 ALMA RB 07#BB 3#8W-01#FULL RBS 3840 TOPO 330620.449 -15.259 58593.8 330591.1593 3 XX YY
2020-09-22 23:51:55 1		s::summary+	7 ALMA RB 07#BB 4#SW-01#FULL RES 128 TOPO 332995.386 -15625.000 2000000.0 332003.1983 4 XX XX
2020-09-22 23:51:55 2		.ms::summary	· · · · · · · · · · · · · · · · · · ·
2020 00 22 22:51:55		TAL CUMPANY	IN NAME OF THE PROPERTY OF THE


plotms(vis='mydata.ms') => plot visibility data




CASA inspection • plotms(vis='mydata.ms') => plot visibility data



CASA inspection plotms(vis='mydata.ms') => plot visibility data






- Datasets can be huge: some tips to reduce (before imaging/plotms)
 - Split out what you need (field, spectral window, channels)
 - Bin in frequency (for continuum)
 - Bin in time domain (if no visibility analysis)


```
[CASA <76>: inp
----> inp()
# split :: Create a visibility subset from an existing visibility set
                    = 'ABAur timebin.ms' # Name of input visibility file
outputvis
                                        # Name of output visibility file
                                        # If the input is a Multi-MS the output
keepmms
                                        # will also be a Multi-MS.
field
                                        # Select field using field id(s) or
                                        # field name(s)
                                        # Select spectral window/channels
                    = '1:100~1000'
spw
scan
                                        # Scan number range
                                           Select data based on antenna/baseline
antenna
correlation
                                        # Select data based on correlation
                                        # Select data based on time range
timerange
intent
                                        # Select observing intent
                                        # Select (sub)array(s) by array ID
array
                                        # number.
                              1.1
                                        # Select data by baseline length.
uvrange
                              1.1
                                        # Select by observation ID(s)
observation
                                        # Multi-feed numbers: Not yet
feed
                                            implemented.
datacolumn
                    = 'corrected'
                                        # Which data column(s) to process.
keepflags
                            True
width
                            3840
                                        # Number of channels to average to form
                                            one output channel
                                           Bin width for time averaging
timebin
     combine
                                           Span the timebin across scan, state
                                            or both
```


Example full spectrum

Molecular lines



Continuum





• Continuum

- Thermal dust emission
- Select channels without line emission and average them using split() command
- Averaging results in much higher SNR
- Clean using specmode='mfs'


• Line

- Molecular line
- Subtract the continuum in the visibility plane using the uvcontsub() command, by specifying channels without line emission
- Clean using specmode='cube'
- Velocity mode: set outframe='LSRK'!
- Set velocity resolution and rest frequency


Molecular lines

- Molecular line spectroscopy
 - Each molecule emits through a number of transitions, depending on local density and temperature
 - Each transition has a unique frequency (fingerprint):
 the <u>rest frequency</u>
 - Molecular lines are broadened by kinematics:
 - Shift by source velocity: few km/s for nearby disks
 - Broadened profile by disk rotation
 - Velocity resolution ALMA can be very high (10 m/s)! Depends on user settings (proposal)
 - Rest frequencies and more: https://splatalogue.online//

Continuum



Cube




(Share screen)

About spectral windows

Practice: output listobs ()


mmary	Spectral	Windows:	(16)	unique	spectral	windows	and :	unique	polaria	zation setup	ıs)		
mary+	SpwID	Name	•	-	•			#Chans	Frame		ChanWid(kHz)	TotBW(kHz)	CtrFreq(MHz)
mary+	19	X11359233	43#ALI	MA_RB_	06#BB_2#S	W-01#FULI	_RES	128	TOPO	233201.518	15625.000	2000000.0	234193.7059
mary+	23	X11359233	43#ALI	MA_RB_	06#BB_4#S	W-01#FULI	_RES	128	TOPO	218493.923	-15625.000	2000000.0	217501.7354
mary+	25	X11359233	43#ALI	MA_RB_	06#BB_1#S	W-01#FULI	_RES	1920	TOPO	230522.724	976.562	1875000.0	231459.7354
mary+	27	X11359233	43#AL	MA_RB_	06#BB_3#S	W-01#FULI	_RES	1920	TOPO	220396.747	-976.562	1875000.0	219459.7354
mary+	47	X11359233	43#ALI	MA_RB_	06#BB_2#S	W-01#FULI	_RES	128	TOPO	233198.091	15625.000	2000000.0	234190.2783
mary+	51	X11359233	43#ALI	MA_RB_	06#BB_4#S	W-01#FULI	L_RES	128	TOPO	218490.620	-15625.000	2000000.0	217498.4328
mary+	53	X11359233	43#ALI	MA_RB_	06#BB_1#S	W-01#FULI	_RES	1920	TOPO	230519.421	976.562	1875000.0	231456.4328
mary+	55	X11359233	43#ALI	MA_RB_	06#BB_3#S	W-01#FULI	_RES	1920	TOPO	220393.445	-976.562	1875000.0	219456.4328
mary+	75	X11359233	43#ALI	MA_RB_	06#BB_2#S	W-01#FULI	_RES	128	TOPO	233194.079	15625.000	2000000.0	234186.2664
mary+	79	X11359233	43#ALI	MA_RB_	06#BB_4#S	W-01#FULI	_RES	128	TOPO	218486.755	-15625.000	2000000.0	217494.5673
mary+	81	X11359233	43#ALI	MA_RB_	06#BB_1#S	W-01#FULI	_RES	1920	TOPO	230515.556	976.562	1875000.0	231452.5673
mary+	83	X11359233	43#ALI	MA_RB_	06#BB_3#S	W-01#FULI	_RES	1920	TOPO	220389.579	-976.562	1875000.0	219452.5673
mary+	103	X11359233	43#AL	MA_RB_	06#BB_2#S	W-01#FULI	_RES	128	TOPO	233193.692	15625.000	2000000.0	234185.8796
mary+	107	X11359233	43#ALI	MA_RB_	06#BB_4#S	W-01#FULI	_RES	128	TOPO	218486.382	-15625.000	2000000.0	217494.1946
mary+	109	X11359233	43#ALI	MA_RB_	06#BB_1#S	W-01#FULI	_RES	1920	TOPO	230515.183	976.562	1875000.0	231452.1946
mary+	111	X11359233	43#ALI	MA_RB_	06#BB_3#S	W-01#FULI	L_RES	1920	TOPO	220389.206	-976.562	1875000.0	219452.1946
mmary	Sources:	17											

About spectral windows




Detections and non-detections


Detection point-source



Detection extended source




Non-detection




Detections

Get information about flux, size, etc. either with viewer or using imfit()



Non-detections/noise



Measure noise in emission-free region

Non-detections/noise


Common Parameters											
Good practice: compare	Declination	-24:00:00.00									
with theoretical noise	Polarisation	Dual 🗸									
	Observing Frequency Observing Band	345									
using ALMA sensitivity		ALMA_RB_07 ~									
	andwidth per Polarization	7.500000	.5000CC								
Calculator	Water Vapour				C Manual Choice						
	Column Density										
	Trx, tau, Tsky	72 K, 0.211, 47.919	2 K, 0.211, 47.919 K								
	Tsys	169.848 K	69.848 K								
Individual Parameters											
	12 m Array				7 m Array			Total Power Array			
Number of Antennas	43		•		10			3			
Resolution	D	✓ arcsec			0 /		arcsec 🕶	9.6			
Sensitivity (rms)	95.62091693992167		✓ uJy ¬		2.8853848046728888	3848046728888		5.246095011230592			
Equivalent to	Unknown			mK 🕶	Unknown mK			0.597			
Integration Time	5		•	min 🕶	60	J	s T	60			
					Integration Time Unit Option	Automatic					
					Sensitivity Unit Option	Automatic	;				
Calculate Inte	gration Time				Calculate Sensitivity						

https://asa.alma.cl/SensitivityCalculator/

Import/export

- For operations outside CASA, export your images to a fitsfile using exportfits()
- For most operations in CASA and CASA viewer, import your images to an image file using importfits() if not yet in fits format


Another useful tool: CARTAVIS



More information

- ALMA proposer's guide: https://almascience.nrao.edu/proposing/proposers-guide
- ALMA CASA tutorials: https://casaguides.nrao.edu/index.php/ALMAguides
- NRAO 17th Synthesis Imaging Workshop 2020: http://www.cvent.com/events/virtual-17th-synthesis-imaging-workshop/ agenda-0d59eb6cd1474978bce811194b2ff961.aspx (online lectures)

- ALMA data becomes public after 1 year and is provided with reduction script and basic reduced fits files!
- ALMA archive: https://almascience.nrao.edu/asax/



Often many datasets: figure out what you need

																			_
190	Obs	ervations (22)	© Proje	ects (13))	☐ Public	ations (43)										□ 🦫	Ø 8	R
_ 0	• ↔	Project code	ALMA source name		Dec		Sitivi	tyRel	ease	date	Ang. res.	esolu		Max. reco. scale	FOV	Scientific category	Science keyw	ord	ln
- 0	·	2011.0.00724.8	LkCa 15	04:39:17.801	+22:21:08	3.227 9	0.78	684.87.892.37GHz	2014-01-09	12	0.26	0.42	12m	2.39	8.46	Disks and planet forma	Disks around	ow-mas	1
_ 0	₩ ↔	2013.1.00226.5	lkca_15	04:39:17.806	+22:21:03	3.290 6	0.08	241.54260.55GHz	2015-08-10	26	0.45	0.14	12m	3.97	23.18	ISM and star formation	Low-mass sta	r formati	1
= 0	↔	2012.1.00 170.5	LkCa_15	04:39:17.806	+22:21:00	3.286 7	0.07	329.21343.00GHz	2015-11-15	2	0.19	0.11	12m	1.80	17.32	Disks and planet forma	Disks around	DW-EIRR	2
- 0	+ ↔	2012.1.008 3.8	LkCa_15	04:39:17.806	+22:21:0	3.288 7	0.02	384.0134Z999Hz	2015-12-02	2	0.20	0.11	12m	1.89	12.08	Disks and planet forma	Disks around	ow-mas	1
= 0	→ ←→	2013.1.00226 S	lkes_15	04:39:17.806	+22:21:00	3.285 6	0.09	216,08235. 7GHz	2016-08-16	26	0.41	0.16	12m	4.47	25.B2	ISM and star formation	Low-mass sta	r formati	1
_ 0	·	2015.1.00657.9	llica16	04:39:12.807	+22/21/08	3.268 7	0.03	275.21.290.98 SHz	2017-03-14	2	0.96	1.17	12m	8.95	20.57	Disks and planet forma	Disks around	ow-mas	1
_ 0	₩ +	2015/1/00657/5	likoa15	04:39:17.807	+22:21:03	3.256 7	0.04	302.06317.819 z	2017-12-29	2	0.53	1.07	12m	5.18	18.78	Disks and planet forma	Disks around	ow-mas	1
0	.	2015.1.00657.5	kea15	04:39:17.807	+22:21:0	3.256 7	0.03	283.46299.20G-	2017-12-29	2	0.56	1.14	12m	5.38	19.99	Disks and planet forma	Disks around	ow-mas	1
_ 0	→ ←→	2015.1.00657.5	N 945	04:39:17.807	+22:21:03	3.256 7	0.05	298.31314.06SHz	2017-12-30	2	0.60	1.08	12m	6.00	19.02	Disks and planet forma	Disks around	ow-mas	1

Hover mouse on program number:

Abstract proposal

Abstract propos
Project title
The origin of transitional disks: grain growth or dynamical clearing by planets?
Pl name
Porez, Loure
Proposal abstract
Most young, low mass stars are surrounded by optically thick appealion disks. A small fraction of these stars show a remarkable depletion of dust in the inner disk regions. These so-called
"Transition disks" are thought to represent a brief, but extremely important, evolutionary phase between young, optically thick protoplanetary disks and old, optically this debrie class. A
number of mechanisms have been proposed to deplete the inner regions of transition disks,
including grain growth, photo-evaporation by the central star, and dynamical clearing by a recently formed planer. Observationally, distinguishing between these mechanisms has been
eifficult up to now. In Pris proposal, we request time with ALMA to image a subset of Pransition

disks with large inner holes, large disk masses, and high accretion rates. that likely originate by either grain growth or dynamical diearing by a planetary object. ALMA's exquisite sensitivity and high angular resolution, already available in Early Science, can resolve the inner disk and detect.

Hover mouse on Frequency: Spectral setup

	Terequency	Resolution	Sensitivity 10Km/s	Sensitivity native	Pal. Product	Туре
e i	329.21.329.453Hz	122 ()/kHz	118mJubeam@10km/s	028.Jyfosam@native	XXYV	line
0-0	330,50330.74GHz	122.07kHz	1.50mJy/beam@10km/s	0.33uJy/peam@native	XXYY	line
	335.02.341.0004z	91250,00kHz	1.49mJy/brang/Ckm/s	0.11. Jy/beam@native	XXYY	continuum
n-s	341.02.343.006Hz	31200.00kHz	1.49mJy/beam@10km/s	0.11.Jybeam@native	XXXX	continuum

Or check directly at publications/projects

Download:

ALMA Request Handler



✓ ↔ 2013.1.00226.S lkca_15


Check what you need

Anonymous User: Request #1653683601122


✓ Request Title: click to edit Download Selected ☑ readme ☑ product ☑ auxiliary □ raw □ raw (semipass) □ external. Project / OUSet / Executionblock Accessible T E E Request 1653683601122 185 MIB ▼ 🧝 🛅 Project 2017.1.00727.8 ▼ ☐ Science Goal OUS uidt/A001/X1296/X66d. Group OUS uid //A001/X12980X68e ▼ 📄 📉 Member OUS uids/A001/X1296/X668 ▶ 88 LkCa15_a_09_TM1 readme memberuid A001 X1296 X661README.tid $3 \, \mathrm{KB}$ 0 ► □ □ product 2017.1.00727.S_uid___A001_X1296_X55f_001_of_001.tar 87 GIB ▶ □ □ auxifary 2017.1.00727.S_uid___A001_X1296_X96f_auxiliary.tar. 1.68 □ naw 84 GIB 2017.1.00727.5_uid___A002_Xe03885_X11ca2.asdm.adm.tar □ □ raw 2017.1.00727.S_uid___A002_Xc02488_X8503.asdm.sdm.far 100 G65 (asacimas) war 👘 📄 2017.1.00727.5_uld ___A002_Xe1142b_X9308.aadm.adm.tar 77 GIB ▼ F and Member OUS uids/A001/X1298/X871 ▶ SB LkCa15_a_09_TM2 incodine 🖟 🖹 member.uid ___A001_X1296_X671.README.bt. 269 B ▶

| In product 2017.1.00727.9 uld A001 X1296 X571 001 of 001.tar ▶ M I auxiliary 2017.1.00727.S uid A001 X1296 X871 auxiliary.tar 181 MiB ☐ j raw 2017.1.00727.5 uld A002 Xd189ef X16o4.aschn.schn.tar 109 GIB

- Select what you need and click Download selected
- Script recommended: easy to continue
- Keep in mind that datasets are huge, 100s of Gb!
 Need storage, also for reduction
- Different Cycles: different CASA versions to reduce



- Full dataset: folder structure
- README: comments reduction, CASA version
- Raw: raw data (ASDM)
- Script: contains main calibration scripts
- QA: quality assessment
- Product: basic reduction: often very large and unnecessary!
- Calibration: calibration tables
- Calibrated: measurement sets (after running script)



- Trick for quick look at product fits files: NAOJ fits archive! https://jvo.nao.ac.jp/portal/top-page.do
- Fill in program number and browse through fits images

ALMA FITS Archive : Project Info

Project Code: 2013.1.00220.S 🗵 ALMA Sci Portal

Show all the data including calibration (*.flux.fits, *.pb.fits, target=J####[+]####), duplicated, and deprecated data.

ımber of data per page : 20 💟

Ordered by dataset_id (desc)

otal number : 78

lotal nu	tal number : 78																		
#	dataset id	all	Download all the checked data	origin 7	image	spect	ra/dec (J2000)	target name	Cube size (XXYxF) 7	Image size (arcmin2)	pixel scale, beam size (arcsec)	band	freq. range (GHz)	freq. scale per pix (MHz)	obs date	release date ?	data type	3rd axis	mem
1	ALMA01024028		Download WebQLv4 VO Search	ALMA official		WWY IN	15h47m50.6 -35d28m35	LupusIII_1002	640 x640 x40 x1	0.32 x0.32	0.030, 0.344 x0.300	Band7	329.304 329.348	1.098		2016- 09-05	CUBE	frequency	A001_X12
2	ALMA01024025		Download WebQLv4 VO Search	ALMA official			15h39m27.7 -34d46m17	Lupusl_4	640 x640 x1 x1	0.32 x0.32	0.030, 0.325 x0.258	Band7	326.285 - 343.660	17,375.016	2015- 06-15	2016- 09-05	IMAGE	frequency	A001_X12
3	ALMA01024024		Download WebQLv4 VO Search	ALMA official		Mila	15h59m25.2 -42d35m07	LupusIV_142	640 x640 x40 x1	0.32 x0.32	0.030, 0.342 x0.314	Band7	329.304 - 329.348	1.098	2015- 06-15	2016- 09-05	CUBE	frequency	A001_X12
4	ALMA01024023	П	Download WebQLv4 VO Search	ALMA official			16h00m07.4 -41d49m48	LupusIV_146	640 x640 x1 x1	0.32 x0.32	0.030, 0.334 x0.271	Band7	326.285 - 343.660	17,375.047	2015- 06-15	2016- 09-05	IMAGE	frequency	A001_X12
5	ALMA01024022		Download WebQLv4 VO Search	ALMA official			15h39m27.7 -34d46m17	Lupust_4	640 x640 x1 x1	0.32 x0.32	0.030, 0.325 x0.258	Band7	326.285 - 343.660	17,375.016	2015- 06-15	2016- 09-05	IMAGE	frequency	A001_X12
6	ALMA01024021		Download WebQl v4 VO Swerch	ALMA official			15h39m27.7 -34d46m17	Lupust_4	640 x640 x1 x1	0.32 x0.32	0.030, 0.325 ×0.258	Band7	326.285 343.660	17,375.016	2015- 06-15	2018- 09-05	IMAGE	frequency	A001_X12
7	ALMA01024018		Download WebQI v4 VO Ssarch	ALMA official			15h58m02.5 -37d36m02	LupusII_1006	640 x640 x1 x1	0.32 x0.32	0.030, 0.335 x0.260	Band7	326.285 - 343.660	17,375.028		2018- 09-05	IMAGE	frequency	A001_X12

- ALMA data is quality assessed (checked for noise/beam size proposal: QA1 and QA2) and basic reduced (product fits files) but often room for improvement
- Possible improvements: additional flagging, combination of configurations, self-calibration, imaging (weighting, velocity resolution, etc.)
- Recommended to download raw data, run calibration script and redo imaging for the purpose of your science.
- Very annoying: many different incompatible CASA versions required. Possible solution next year with ARCADE environment.
- Product fits files can be used for initial inspection, but often not science ready

Now it's your turn!



WE WANT YOU!

TO REDUCE ALMA DATA

ALMA reduction

- Today: ALMA CASA tutorial TW Hya
 - Download and install CASA
 - https://casaguides.nrao.edu/index.php/ALMAguides
 - A first look at imaging in CASA 6.4: This guide gives a first look at imaging and image analysis in CASA.
 - A first look at self-calibration in CASA 6.4: This guide demonstrates continuum self-cal.
 - A first look at spectral line imaging in CASA 6.4: This guide shows imaging of a spectral line.
 - = A first look at image analysis in CASA 6.4: This guide demonstrates moment creation and basic image analysis.
- Tomorrow: pick your project from an unpublished dataset with many resolved protoplanetary disks (already calibrated and split out science targets: start directly from the measurement set)
 - => goal: produce images, analyse them and present on Friday!

Questions?

Dr. Nienke van der Marel <u>astro@nienkevandermarel.com</u> http://www.nienkevandermarel.com